

# CE-EMC TEST REPORT

**Prepared for :**

**EDA Technology Shanghai Co.,Ltd**

**Building 29, No.1661 Jialuo Road, Jiading District, Shanghai, PRC**

**Product Name: CM5 AI CAMERA**

**Trade Mark: EDATEC**

**Product Model (S): ED-AIC3000**

**Date of Test: Dec. 15, 2025 – Jan. 06, 2026**

**Date of Report: Jan. 06, 2026**

**Report Number: HK2512156528-1ER**

**Prepared By :**

**Shenzhen HUAK Testing Technology Co., Ltd.**

**1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,  
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com**

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



## HUAK TESTING

## TEST REPORT VERIFICATION

Applicant : EDA Technology Shanghai Co.,Ltd  
Address : Building 29, No.1661 Jialuo Road, Jiading District, Shanghai, PRC  
Manufacturer : EDA Technology Shanghai Co.,Ltd  
Address : Building 29, No.1661 Jialuo Road, Jiading District, Shanghai, PRC  
Product Name : CM5 AI CAMERA  
(A) Product Model : ED-AIC3000  
(B) Series Model : N/A  
(C) Power Supply : DC 24V From Adapter with AC 100-240V, 50/60Hz

EN 55032:2015 + A1:2020 + A11:2020

EN IEC 61000-3-2:2019 + A1:2021 + A2:2024

EN 61000-3-3:2013 + A1:2019 + A2:202

EN 55035:2017+A11:2020

This device described above has been tested by HUAK, and the test results show that the equipment under test (EUT) is in compliance with the 2014/30/EU requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of HUAK, this document may be altered or revised by HUAK, personal only, and shall be noted in the revision of the document.

Test Result..... **Pass**

Date of Test:

Dec. 15, 2025 – Jan. 06, 2026

Prepared by:

Kevin Pan

Reviewed by:

Shiley Wom

Approved by:

## Technical Director

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel: +86-0755-2302 9901 E-mail: info@huak.com Web: www.huak.com

Shenzhen HUAK Testing Technology Co., Ltd. Tel: +86-0755-2302 9901 E-mail: info@huak.com Web: www.huak.com Add: 1-3/F, Building B2, Jinfeng Zhongcheng Zhizhi Innovation Park, Heping, Futian Street, Beicun District, Shenzhen, Guangdong, China

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING

## Table of Contents

|                                                             | Page |
|-------------------------------------------------------------|------|
| 1 . TEST SUMMARY                                            | 7    |
| 1.1 TEST FACILITY                                           | 8    |
| 1.2 MEASUREMENT UNCERTAINTY                                 | 8    |
| 2 . GENERAL INFORMATION                                     | 9    |
| 2.1 GENERAL DESCRIPTION OF EUT                              | 9    |
| 2.2 DESCRIPTION OF TEST MODES                               | 10   |
| 2.3 DESCRIPTION OF TEST SETUP                               | 11   |
| 2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL          | 12   |
| 2.5 MEASUREMENT INSTRUMENTS LIST                            | 13   |
| 3 . EMC EMISSION TEST                                       | 15   |
| 3.1 CONDUCTED EMISSION MEASUREMENT                          | 15   |
| 3.1.1 POWER LINE CONDUCTED EMISSION                         | 15   |
| 3.1.2 Telecommunication Ports CONDUCTED EMISSION            | 15   |
| 3.1.3 TEST PROCEDURE                                        | 16   |
| 3.1.4 TEST SETUP                                            | 16   |
| 3.1.5 EUT OPERATING CONDITIONS                              | 16   |
| 3.1.6 TEST RESULTS                                          | 17   |
| 3.2 RADIATED EMISSION MEASUREMENT                           | 20   |
| 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT (30~1000MHz)  | 20   |
| 3.2.2 LIMITS OF RADIATED EMISSION MEASUREMENT(1000~6000MHz) | 20   |
| 3.2.3 TEST PROCEDURE                                        | 20   |
| 3.2.4 TEST SETUP                                            | 21   |
| 3.2.5 EUT OPERATING CONDITIONS                              | 21   |
| 3.2.6 TEST RESULTS(30~1000MHz)                              | 22   |
| 3.2.7 TEST RESULTS(1000~6000MHz)                            | 24   |
| 3.3 HARMONICS CURRENT                                       | 26   |
| 3.3.1 LIMITS OF HARMONICS CURRENT                           | 26   |
| 3.3.2 TEST PROCEDURE                                        | 27   |
| 3.3.3 EUT OPERATING CONDITIONS                              | 27   |
| 3.3.4 TEST SETUP                                            | 27   |
| 3.3.5 TEST RESULTS                                          | 28   |
| 3.4 VOLTAGE FLUCTUATION AND FLICKERS                        | 29   |
| 3.4.1 LIMITS OF VOLTAGE FLUCTUATION AND FLICKERS            | 29   |
| 3.4.2 TEST PROCEDURE                                        | 29   |
| 3.4.3 EUT OPERATING CONDITIONS                              | 30   |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING




HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING

## Table of Contents

## Page

|                                                 |           |
|-------------------------------------------------|-----------|
| 3.4.4 TEST SETUP                                | 30        |
| 3.4.5 TEST RESULTS                              | 31        |
| <b>4 . EMC IMMUNITY TEST</b>                    | <b>32</b> |
| 4.1 STANDARD COMPLIANCE/SEVERITY LEVEL/CRITERIA | 32        |
| 4.2 GENERAL PERFORMANCE CRITERIA                | 33        |
| 4.3 GENERAL PERFORMANCE CRITERIA TEST SETUP     | 33        |
| 4.4 ESD TESTING                                 | 34        |
| 4.4.1 TEST SPECIFICATION                        | 34        |
| 4.4.2 TEST PROCEDURE                            | 34        |
| 4.4.3 TEST SETUP                                | 35        |
| 4.4.4 TEST RESULTS                              | 36        |
| 4.5 RS TESTING                                  | 37        |
| 4.5.1 TEST SPECIFICATION                        | 37        |
| 4.5.2 TEST PROCEDURE                            | 37        |
| 4.5.3 TEST SETUP                                | 38        |
| 4.5.4 TEST RESULTS                              | 39        |
| 4.6 EFT/BURST TESTING                           | 40        |
| 4.6.1 TEST SPECIFICATION                        | 40        |
| 4.6.2 TEST PROCEDURE                            | 40        |
| 4.6.3 TEST SETUP                                | 41        |
| 4.6.4 TEST RESULTS                              | 42        |
| 4.7 SURGE TESTING                               | 43        |
| 4.7.1 TEST SPECIFICATION                        | 43        |
| 4.7.2 TEST PROCEDURE                            | 43        |
| 4.7.3 TEST SETUP                                | 44        |
| 4.7.4 TEST RESULTS                              | 45        |
| 4.8 INJECTION CURRENT TESTING                   | 46        |
| 4.8.1 TEST SPECIFICATION                        | 46        |
| 4.8.2 TEST PROCEDURE                            | 46        |
| 4.8.3 TEST SETUP                                | 47        |
| 4.8.4 TEST RESULTS                              | 48        |
| 4.9 POWER FREQUENCY MAGNETIC FIELD TESTING      | 49        |
| 4.9.1 TEST SPECIFICATION                        | 49        |
| 4.9.2 TEST PROCEDURE                            | 49        |
| 4.9.3 TEST SETUP                                | 50        |
| 4.9.4 TEST RESULTS                              | 51        |
| 4.10 VOLTAGE INTERRUPTION/DIPS TESTING          | 52        |
| 4.10.1 TEST SPECIFICATION                       | 52        |
| 4.10.2 TEST PROCEDURE                           | 52        |



**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

## Table of Contents

|                               | Page |
|-------------------------------|------|
| 4.10.3 TEST SETUP             | 52   |
| 4.10.4 TEST RESULTS           | 53   |
| 5 . EUT TEST PHOTO            | 54   |
| ATTACHMENT PHOTOGRAPHS OF EUT | 58   |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING



HUAK TESTING

HUAK TESTING



HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

### \*\* Issued history \*\*

| Revision     | Description                 | Issued Date | Remark     |
|--------------|-----------------------------|-------------|------------|
| Revision 1.0 | Initial Test Report Release | 2026/01/06  | Jason Zhou |
|              |                             |             |            |
|              |                             |             |            |



**HUAK TESTING**  
HUAK TESTING

## 1. TEST SUMMARY

Test procedures according to the technical standards:

| EMC Emission        |                                             |                         |                 |        |
|---------------------|---------------------------------------------|-------------------------|-----------------|--------|
| Standard            | Test Item                                   | Limit                   | Judgment        | Remark |
| EN 55032            | Conducted Emission (AC port)                | Class A<br>NOTE (5)     | PASS            |        |
|                     | Conducted Emission (Telecommunication port) | Class A                 | PASS            |        |
|                     | Radiated Emission                           | Class A                 | PASS            |        |
| EN IEC 61000-3-2    | Harmonic Current Emission                   | Class A                 | N/A<br>NOTE (2) |        |
| EN 61000-3-3        | Voltage Fluctuations & Flicker              | -----                   | PASS            |        |
| EMC Immunity        |                                             |                         |                 |        |
| Section<br>EN 55035 | Test Item                                   | Performance<br>Criteria | Judgment        | Remark |
| EN 61000-4-2        | Electrostatic Discharge                     | B                       | PASS            |        |
| EN IEC 61000-4-3    | RF electromagnetic field                    | A                       | PASS            |        |
| EN 61000-4-4        | Fast transients                             | B                       | PASS            |        |
| EN 61000-4-5        | Surges                                      | B                       | PASS            |        |
| EN IEC 61000-4-6    | Injected Current                            | A                       | PASS            |        |
| EN 61000-4-8        | Power Frequency Magnetic Field              | A                       | N/A             |        |
| EN IEC 61000-4-11   | Volt. Interruptions Volt. Dips              | B / C / C<br>NOTE (3)   | PASS            |        |

### NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) The power consumption of EUT is less than 75W and no Limits apply.
- (3) Voltage dip: 100% reduction – Performance Criteria **B**  
Voltage dip: 30% reduction – Performance Criteria **C**  
Voltage Interruption: 100% Interruption – Performance Criteria **C**
- (4) For client's request and manual description, the test will not be executed.
- (5) Equipment meeting Class A requirements may not offer adequate protection to broadcast services within a residential environment.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING



## 1.1 TEST FACILITY

Shenzhen HUAK Testing Technology Co., Ltd.

Address: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  · where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  · providing a level of confidence of approximately 95 % .

### A. Conducted Measurement :

| Measurement Frequency Range | Uncertainty | NOTE |
|-----------------------------|-------------|------|
| 150kHz ~ 30MHz              | ±2.71dB     |      |

### B. Radiated Measurement :

| Measurement Frequency Range | Uncertainty | NOTE |
|-----------------------------|-------------|------|
| 30 ~ 1000MHz                | ±3.90dB     |      |
| 1 ~ 6GHz                    | ±4.28dB     |      |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



## HUAK TESTING

## 2. GENERAL INFORMATION

## 2.1 GENERAL DESCRIPTION OF EUT

|                      |                                                                                                                                                                   |                      |     |                      |     |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----|----------------------|-----|
| Product Name         | CM5 AI CAMERA                                                                                                                                                     |                      |     |                      |     |
| Product Model        | ED-AIC3000                                                                                                                                                        |                      |     |                      |     |
| Series Model         | N/A                                                                                                                                                               |                      |     |                      |     |
| Model Difference     | N/A                                                                                                                                                               |                      |     |                      |     |
| Product Description  | <p>The EUT is a CM5 AI CAMERA.</p> <table border="1"><tr><td>Operating frequency:</td><td>N/A</td></tr><tr><td>Connecting I/O port:</td><td>N/A</td></tr></table> | Operating frequency: | N/A | Connecting I/O port: | N/A |
| Operating frequency: | N/A                                                                                                                                                               |                      |     |                      |     |
| Connecting I/O port: | N/A                                                                                                                                                               |                      |     |                      |     |
| Power Source         | DC Voltage                                                                                                                                                        |                      |     |                      |     |
| Power Rating         | DC 24V From Adapter with AC 100-240V, 50/60Hz                                                                                                                     |                      |     |                      |     |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F, Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.

## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-------------|
| Mode 1       | Working     |

| For Conducted Test |             |
|--------------------|-------------|
| Final Test Mode    | Description |
| Mode 1             | Working     |

| For Radiated Test |             |
|-------------------|-------------|
| Final Test Mode   | Description |
| Mode 1            | Working     |

| For EMS Test    |             |
|-----------------|-------------|
| Final Test Mode | Description |
| Mode 1          | Working     |



**HUAK TESTING**

HUAK TESTING


HUAK TESTING

HUAK TESTING

HUAK TESTING

## 2.3 DESCRIPTION OF TEST SETUP

Mode 1:



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



## HUAK TESTING

## 2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Shielded Type                                                                                    | Ferrite Core                                                                                     | Length | Note                                                                                               |
|------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------------|
|      |  HUAK TESTING |  HUAK TESTING |        |                                                                                                    |
|      |                                                                                                  |                                                                                                  |        |                                                                                                    |
|      |                                                                                                  |               |        |  HUAK TESTING |
|      |  HUAK TESTING |  HUAK TESTING |        |                                                                                                    |
|      |                                                                                                  |                                                                                                  |        |                                                                                                    |
|      |                                                                                                  |               |        |  HUAK TESTING |
|      |                                                                                                  |                                                                                                  |        |                                                                                                    |
|      |  HUAK TESTING |  HUAK TESTING |        |                                                                                                    |
|      |                                                                                                  |                                                                                                  |        |                                                                                                    |
|      |                                                                                                  |               |        |  HUAK TESTING |
|      |                                                                                                  |                                                                                                  |        |                                                                                                    |
|      |  HUAK TESTING |  HUAK TESTING |        |                                                                                                    |
|      |                                                                                                  |                                                                                                  |        |                                                                                                    |

**Note:**

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

(3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



## 2.5 MEASUREMENT INSTRUMENTS LIST

### 2.5.1 CONDUCTED TEST SITE

| Item | Kind of Equipment       | Manufacturer | Type No.             | Serial No. | Calibrated until |
|------|-------------------------|--------------|----------------------|------------|------------------|
| 1    | LISN                    | R&S          | ENV216               | HKE-002    | Feb. 18, 2026    |
| 2    | LISN                    | R&S          | ENV216               | HKE-059    | Feb. 18, 2026    |
| 3    | EMI Test Receiver       | R&S          | ESR-7                | HKE-005    | Feb. 18, 2026    |
| 4    | ISN                     | ETC          | 08-06-BAC-0<br>22-02 | HKE-062    | Feb. 18, 2026    |
| 5    | Conducted test software | Tonscend     | JS32-CE<br>2.5.0.6   | HKE-081    | /                |

## 2.5.2 RADIATED TEST SITE

| Item | Kind of Equipment      | Manufacturer | Type No.      | Serial No. | Calibrated until |
|------|------------------------|--------------|---------------|------------|------------------|
| 1    | Broadband antenna      | Schwarzbeck  | VULB 9163     | HKE-012    | Feb. 20, 2026    |
| 2    | Horn antenna           | Schwarzbeck  | 9120D         | HKE-013    | Feb. 20, 2026    |
| 3    | EMI Test Receiver      | R&S          | ESR-7         | HKE-010    | Feb. 18, 2026    |
| 4    | Spectrum Analyzer      | Agilent      | N9020A        | HKE-048    | Feb. 18, 2026    |
| 5    | Amplifier              | Schwarzbeck  | EMC051845 SE  | HKE-006    | Feb. 18, 2026    |
| 6    | Amplifier              | Agilent      | 83051A        | HKE-016    | Feb. 18, 2026    |
| 7    | Radiated test software | Tonscend     | JS32-RE 5.0.0 | HKE-082    | /                |

### 2.5.3 HARMONICS AND FILCK

| Item | Kind of Equipment       | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------------|--------------|----------|------------|------------------|
| 1    | Harmonic flicker tester | emtest       | DPA 500N | HKE-037    | Feb. 18, 2026    |

## 2.5.4 ESD

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | ESD device        | TESEQ        | NSG437   | HKE-023    | Feb. 18, 2026    |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**HUAK TESTING**

HUAK TESTING

**2.5.5 RS**

| Item | Kind of Equipment       | Manufacturer | Type No.           | Serial No. | Calibrated until |
|------|-------------------------|--------------|--------------------|------------|------------------|
| 1    | Power amplifier         | micotop      | MPA-80-1000-250    | HKE-142    | Feb. 18, 2026    |
| 2    | Power amplifier         | micotop      | MPA-1000-600 0-100 | HKE-143    | Feb. 18, 2026    |
| 3    | Power Meter             | KEYSIGHT     | E4419B             | HKE-144    | Feb. 18, 2026    |
| 4    | Vector signal generator | KEYSIGHT     | N5182B             | HKE-124    | Feb. 18, 2026    |
| 5    | Field strength probe    | NARDA        | EP601              | HKE-146    | Feb. 18, 2026    |
| 6    | High gain antenna       | Schwarzbeck  | STPL9129           | HKE-147    | Feb. 19, 2026    |
| 7    | RS test software        | Tonscend     | JS35-RS 5.0.0      | HKE-186    | /                |

**2.5.6 SURGE, EFT/BURST, VOLTAGE INTERRUPTION/DIPS**

| Item | Kind of Equipment                             | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-----------------------------------------------|--------------|----------|------------|------------------|
| 1    | Magnetic clamp                                | TESEQ        | EML-20   | HKE-114    | Feb. 18, 2026    |
| 2    | Integrated Conduction Sensitivity Test System | FRANKONIA    | CCIT-10  | HKE-033    | Feb. 18, 2026    |
| 3    | Coupling decoupling network                   | TESEQ        | CDM316   | HKE-032    | Feb. 18, 2026    |

**2.5.8 MF**

| Item | Kind of Equipment              | Manufacturer | Type No.   | Serial No. | Calibrated until |
|------|--------------------------------|--------------|------------|------------|------------------|
| 1    | Power frequency induction coil | LIONCEL      | PMF-801C-C | HKE-049    | Feb. 18, 2026    |








**HUAK TESTING**  
HUAK TESTING

### 3.1.6 TEST RESULTS

|                |                     |                     |            |
|----------------|---------------------|---------------------|------------|
| EUT :          | CM5 AI CAMERA       | Model Name. :       | ED-AIC3000 |
| Temperature :  | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :     | 1010hPa             | Test Date :         | 2025-12-18 |
| Test Mode :    | Mode 1              | Phase :             | L          |
| Test Voltage : | DC 24V From Adapter |                     |            |



| Suspected List |             |                    |             |                    |             |                      |          |      |
|----------------|-------------|--------------------|-------------|--------------------|-------------|----------------------|----------|------|
| NO.            | Freq. [MHz] | Level [dB $\mu$ V] | Factor [dB] | Limit [dB $\mu$ V] | Margin [dB] | Reading [dB $\mu$ V] | Detector | Type |
| 1              | 0.1545      | 50.42              | 19.56       | 79.00              | 28.58       | 30.86                | PK       | L    |
| 2              | 0.3255      | 44.80              | 19.85       | 79.00              | 34.20       | 24.95                | PK       | L    |
| 3              | 0.6225      | 38.71              | 19.73       | 73.00              | 34.29       | 18.98                | PK       | L    |
| 4              | 2.0220      | 41.17              | 20.15       | 73.00              | 31.83       | 21.02                | PK       | L    |
| 5              | 10.0365     | 40.34              | 21.17       | 73.00              | 32.66       | 19.17                | PK       | L    |
| 6              | 13.4880     | 42.13              | 21.62       | 73.00              | 30.87       | 20.51                | PK       | L    |

Remark: Margin = Limit – Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



|                |                     |                     |            |
|----------------|---------------------|---------------------|------------|
| EUT :          | CM5 AI CAMERA       | Model Name. :       | ED-AIC3000 |
| Temperature :  | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :     | 1010hPa             | Test Date :         | 2025-12-18 |
| Test Mode :    | Mode 1              | Phase :             | N          |
| Test Voltage : | DC 24V From Adapter |                     |            |



| Suspected List |             |              |             |              |             |                |          |      |
|----------------|-------------|--------------|-------------|--------------|-------------|----------------|----------|------|
| NO.            | Freq. [MHz] | Level [dBμV] | Factor [dB] | Limit [dBμV] | Margin [dB] | Reading [dBμV] | Detector | Type |
| 1              | 0.1590      | 49.12        | 19.81       | 79.00        | 29.88       | 29.51          | PK       | N    |
| 2              | 0.3165      | 43.75        | 19.69       | 79.00        | 35.25       | 24.06          | PK       | N    |
| 3              | 0.8745      | 40.51        | 19.76       | 73.00        | 32.49       | 20.75          | PK       | N    |
| 4              | 1.4145      | 40.61        | 19.85       | 73.00        | 32.39       | 20.76          | PK       | N    |
| 5              | 1.9275      | 39.98        | 19.93       | 73.00        | 33.02       | 20.05          | PK       | N    |
| 6              | 13.8300     | 40.27        | 21.55       | 73.00        | 32.73       | 18.72          | PK       | N    |


Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



|                |                     |                     |            |
|----------------|---------------------|---------------------|------------|
| EUT :          | CM5 AI CAMERA       | Model Name. :       | ED-AIC3000 |
| Temperature :  | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :     | 1010hPa             | Test Date :         | 2025-12-18 |
| Test Mode :    | Mode 1              | Phase :             | ISN        |
| Test Voltage : | DC 24V From Adapter |                     |            |



### Suspected List

| NO. | Freq. [MHz] | Level [dB $\mu$ V] | Factor [dB] | Limit [dB $\mu$ V] | Margin [dB] | Reading [dB $\mu$ V] | Detector | Type |
|-----|-------------|--------------------|-------------|--------------------|-------------|----------------------|----------|------|
| 1   | 0.5685      | 81.13              | 20.02       | 87.00              | 5.87        | 81.11                | PK       | ISN  |
| 2   | 0.7980      | 81.08              | 19.92       | 87.00              | 5.92        | 81.16                | PK       | ISN  |
| 3   | 0.9825      | 80.29              | 19.87       | 87.00              | 6.71        | 80.42                | PK       | ISN  |
| 4   | 1.2120      | 78.63              | 19.85       | 87.00              | 8.37        | 58.78                | PK       | ISN  |
| 5   | 1.3965      | 77.33              | 19.83       | 87.00              | 9.67        | 57.50                | PK       | ISN  |
| 6   | 2.6430      | 76.31              | 19.79       | 87.00              | 10.69       | 56.52                | PK       | ISN  |

Remark: Margin = Limit – Level

Correction factor = Cable loss + ISN insertion loss

Level=Test receiver reading + correction factor








## 3.2.6 TEST RESULTS(30~1000MHz)

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              | Polarization :      | Horizontal |
| Test Power :  | DC 24V From Adapter |                     |            |



| Suspected List |             |             |                  |                |                |             |             |           |            |
|----------------|-------------|-------------|------------------|----------------|----------------|-------------|-------------|-----------|------------|
| NO.            | Freq. [MHz] | Factor [dB] | Reading [dBμV/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity   |
| 1              | 89.229229   | -21.68      | 49.88            | 28.20          | 50.00          | 21.80       | 100         | 27        | Horizontal |
| 2              | 143.60360   | -17.64      | 43.35            | 25.71          | 50.00          | 24.29       | 100         | 190       | Horizontal |
| 3              | 249.43943   | -19.32      | 49.63            | 30.31          | 57.00          | 26.69       | 100         | 147       | Horizontal |
| 4              | 320.32032   | -16.94      | 48.64            | 31.70          | 57.00          | 25.30       | 100         | 79        | Horizontal |
| 5              | 398.96896   | -15.10      | 50.15            | 35.05          | 57.00          | 21.95       | 100         | 91        | Horizontal |
| 6              | 499.94995   | -13.26      | 47.89            | 34.63          | 57.00          | 22.37       | 100         | 249       | Horizontal |

## Final Data List


Remark: Factor = Cable loss + Antenna factor – Preamplifier; Level = Reading + Factor; Margin = Limit – Level;

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              | Polarization :      | Vertical   |
| Test Power :  | DC 24V From Adapter |                     |            |



| Suspected List |             |             |                        |                      |                      |             |             |           |          |
|----------------|-------------|-------------|------------------------|----------------------|----------------------|-------------|-------------|-----------|----------|
| NO.            | Freq. [MHz] | Factor [dB] | Reading [dB $\mu$ V/m] | Level [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1              | 81.461461   | -21.75      | 57.43                  | 35.68                | 50.00                | 14.32       | 100         | 237       | Vertical |
| 2              | 90.2002     | -21.69      | 60.12                  | 38.43                | 50.00                | 11.57       | 100         | 359       | Vertical |
| 3              | 143.60360   | -17.64      | 50.64                  | 33.00                | 50.00                | 17.00       | 100         | 281       | Vertical |
| 4              | 163.99399   | -17.44      | 49.02                  | 31.58                | 50.00                | 18.42       | 100         | 250       | Vertical |
| 5              | 399.93994   | -15.07      | 50.45                  | 35.38                | 57.00                | 21.62       | 100         | 334       | Vertical |
| 6              | 567.91791   | -12.49      | 43.52                  | 31.03                | 57.00                | 25.97       | 100         | 350       | Vertical |

### Final Data List

Remark: Factor = Cable loss + Antenna factor – Preamplifier; Level = Reading + Factor; Margin = Limit – Level;

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**  
HUAK TESTING


HUAK TESTING

HUAK TESTING

HUAK TESTING

### 3.2.7 TEST RESULTS(1000~6000MHz)

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              | Polarization :      | Horizontal |
| Test Power :  | DC 24V From Adapter |                     |            |



| Suspected Data List |             |                  |                   |             |                   |                |             |           |            |
|---------------------|-------------|------------------|-------------------|-------------|-------------------|----------------|-------------|-----------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV/m] | PK Level [dBμV/m] | Factor [dB] | PK Limit [dBμV/m] | PK Margin [dB] | Height [cm] | Angle [°] | Polarity   |
| 1                   | 1125.012    | 52.77            | 33.57             | -19.20      | 80.00             | 46.43          | 100         | 290       | Horizontal |
| 2                   | 1369.036    | 53.28            | 34.51             | -18.77      | 80.00             | 45.49          | 100         | 300       | Horizontal |
| 3                   | 1667.066    | 53.07            | 34.46             | -18.61      | 80.00             | 45.54          | 100         | 220       | Horizontal |
| 4                   | 2374.537    | 53.81            | 39.11             | -14.70      | 80.00             | 40.89          | 100         | 130       | Horizontal |
| 5                   | 3230.723    | 53.70            | 39.64             | -14.06      | 80.00             | 40.36          | 100         | 210       | Horizontal |
| 6                   | 4291.029    | 53.42            | 42.12             | -11.30      | 80.00             | 37.88          | 100         | 170       | Horizontal |


Remark: Factor = Cable loss + Antenna factor – Preamplifier; Level = Reading + Factor; Margin = Limit – Level;

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.7 °C             | Relative Humidity : | 51%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              | Polarization :      | Vertical   |
| Test Power :  | DC 24V From Adapter |                     |            |



| Suspected Data List |             |                  |                   |             |                   |                |             |           |          |
|---------------------|-------------|------------------|-------------------|-------------|-------------------|----------------|-------------|-----------|----------|
| NO.                 | Freq. [MHz] | Reading [dBμV/m] | PK Level [dBμV/m] | Factor [dB] | PK Limit [dBμV/m] | PK Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1                   | 1387.038    | 53.52            | 34.90             | -18.62      | 80.00             | 45.10          | 100         | 200       | Vertical |
| 2                   | 1870.287    | 53.44            | 35.62             | -17.82      | 80.00             | 44.38          | 100         | 160       | Vertical |
| 3                   | 2488.148    | 54.13            | 39.57             | -14.56      | 80.00             | 40.43          | 100         | 70        | Vertical |
| 4                   | 3134.713    | 53.77            | 39.65             | -14.12      | 80.00             | 40.35          | 100         | 190       | Vertical |
| 5                   | 4119.411    | 54.07            | 42.26             | -11.81      | 80.00             | 37.74          | 100         | 100       | Vertical |
| 6                   | 4940.594    | 52.81            | 43.10             | -9.71       | 80.00             | 36.90          | 100         | 320       | Vertical |

Remark: Factor = Cable loss + Antenna factor – Preamplifier; Level = Reading + Factor; Margin = Limit – Level;

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**  
HUAk TESTING

### 3.3 HARMONICS CURRENT

#### 3.3.1 LIMITS OF HARMONICS CURRENT

**Table 1 – Limits for Class A equipment**

| Harmonic order<br><i>h</i> | Maximum permissible<br>harmonic current<br>A |
|----------------------------|----------------------------------------------|
| <b>Odd harmonics</b>       |                                              |
| 3                          | 2,30                                         |
| 5                          | 1,14                                         |
| 7                          | 0,77                                         |
| 9                          | 0,40                                         |
| 11                         | 0,33                                         |
| 13                         | 0,21                                         |
| $15 \leq h \leq 39$        | $0,15 \frac{15}{h}$                          |
| <b>Even harmonics</b>      |                                              |
| 2                          | 1,08                                         |
| 4                          | 0,43                                         |
| 6                          | 0,30                                         |
| $8 \leq h \leq 40$         | $0,23 \frac{8}{h}$                           |

**Table 3 – Limits for Class D equipment**

| Harmonic order<br><i>h</i>                  | Maximum permissible<br>harmonic current per<br>watt<br>mA/W | Maximum permissible<br>harmonic current<br>A |
|---------------------------------------------|-------------------------------------------------------------|----------------------------------------------|
| 3                                           | 3,4                                                         | 2,30                                         |
| 5                                           | 1,9                                                         | 1,14                                         |
| 7                                           | 1,0                                                         | 0,77                                         |
| 9                                           | 0,5                                                         | 0,40                                         |
| 11                                          | 0,35                                                        | 0,33                                         |
| $13 \leq h \leq 39$<br>(odd harmonics only) | $\frac{3,85}{h}$                                            | See Table 1                                  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China





**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING


### 3.3.5 TEST RESULTS

|               |               |                     |            |
|---------------|---------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA | Model Name :        | ED-AIC3000 |
| Temperature : | N/A           | Relative Humidity : | N/A        |
| Pressure :    | N/A           | Test Date :         | N/A        |
| Test Mode :   | N/A           |                     |            |
| Test Power :  | N/A           |                     |            |

Note: EUT power is less than 75W, so this test report is not applicable.



HUAK TESTING



HUAK TESTING



HUAK TESTING



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

### 3.4 VOLTAGE FLUCTUATION AND FLICKERS

#### 3.4.1 LIMITS OF VOLTAGE FLUCTUATION AND FLICKERS

The limits shall be applicable to voltage fluctuations and flicker at the supply terminals of the equipment under test, measured or calculated according to Clause 4 under test conditions described in Clause 6 and Annex A.

Tests made to prove compliance with the limits are considered to be type tests.

The following limits apply:

the value of  $P_{st}$  shall not be greater than 1.0;

the value of  $P$  shall not be greater than 0.65;

$T_{max}$ , the accumulated time value of  $d(t)$  with a deviation exceeding 3.3 % during a single voltage change at the EUT terminals, shall not exceed 500 ms;

the maximum relative steady-state voltage change,  $d_c$ , shall not exceed 3.3 %;

the maximum relative voltage change  $d_{max}$ , shall not exceed:

a) 4% without additional conditions;

b) 6% for equipment which is:

switched manually, or

switched automatically more frequently than twice per day, and also has either a delayed restart (the delay being not less than a few tens of seconds), or manual restart, after a power supply interruption.

NOTE The cycling frequency is further limited by the  $P$  and  $P_{st}$  limits. For example: a  $d_{max}$  of 6 % producing a rectangular voltage change characteristic twice per hour gives a  $P$  of about 0.65.

c) 7% for equipment which is: attended whilst in use (for example: hair dryers, vacuum cleaners, kitchen equipment such as mixers, garden equipment such as lawn mowers, portable tools such as electric drills), or switched on automatically, or is intended to be switched on manually, no more than twice per day, and also has either a delayed restart (the delay being not less than a few tens of seconds) or manual restart, after a power supply interruption.

In the case of equipment having several separately controlled circuits in accordance with 6.6, limits b) and c) shall apply only if there is delayed or manual restart after a power supply interruption; for all equipment with automatic switching which is energized immediately on restoration of supply after a power supply interruption, limits a) shall apply.

For all equipment with manual switching, limits b) or c) shall apply depending on the rate of switching typical of normal operation.

#### 3.4.2 TEST PROCEDURE

##### a. Harmonic Current Test:

Test was performed according to the procedures specified in Clause 5.0 of IEC555-2 and/or Sub-clause 6.2 of IEC/EN IEC 61000-3-2 depend on which standard adopted for compliance measurement.

##### b. Fluctuation and Flickers Test:

Tests was performed according to the Test Conditions/Assessment of Voltage Fluctuations specified in Clause 5.0/6.0 of IEC555-3 and/or Clause 6.0/4.0 of IEC/EN 61000-3-3 depend on which standard adopted for compliance measurement.

c. All types of harmonic current and/or voltage fluctuation in this report are assessed by direct measurement using flicker-meter.



**HUAK TESTING**

HUAK TESTING

HUAK TESTING


HUAK TESTING

HUAK TESTING

### 3.4.3 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.

### 3.4.4 TEST SETUP





**HUAK TESTING**  
HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

### 3.4.5 TEST RESULTS

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.5 °C             | Relative Humidity : | 51%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              |                     |            |
| Test Power :  | DC 24V From Adapter |                     |            |
| Test Result:  | Pass                |                     |            |

| Flicker Measurements |                 |                     |                    |                      |                      |
|----------------------|-----------------|---------------------|--------------------|----------------------|----------------------|
|                      | P <sub>lt</sub> | Max P <sub>st</sub> | Max D <sub>c</sub> | Max D <sub>max</sub> | Max T <sub>max</sub> |
| Line 1:              | 0.012           | 0.028               | 0                  | < 0.2                | 0                    |
| Limits:              | 0.65            | 1                   | 3.3                | 4                    | 0.5                  |
| Results:             | PASS            | PASS                | PASS               | PASS                 | PASS                 |



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

## 4. EMC IMMUNITY TEST

### 4.1 STANDARD COMPLIANCE/SEVERITY LEVEL/CRITERIA

| Tests Standard No.                                            | TEST SPECIFICATION                                                                                                                                      | Test Mode Test Ports      | Perform. Criteria |
|---------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------|
| 1. ESD<br>IEC/EN 61000-4-2                                    | 8KV air discharge<br>4KV contact discharge                                                                                                              | Direct Mode               | B                 |
|                                                               | 4KV HCP discharge<br>4KV VCP discharge                                                                                                                  | Indirect Mode             | B                 |
| 2. RS<br>IEC/EN IEC 61000-4-3                                 | 80 MHz to 1000 MHz,<br>1800( $\pm 1\%$ )MHz,<br>2600( $\pm 1\%$ )MHz,<br>3500( $\pm 1\%$ )MHz,<br>5000( $\pm 1\%$ )MHz,<br>1000Hz, 80%,<br>AM modulated | Enclosure                 | A                 |
| 3. EFT/Burst<br>IEC/EN 61000-4-4                              | 5/50ns Tr/Th<br>5kHz Repetition Freq.                                                                                                                   | Power Supply Port         | B                 |
|                                                               | 5/50ns Tr/Th<br>5kHz Repetition Freq.                                                                                                                   | CTL/Signal Data Line Port | B                 |
| 4. Surges<br>IEC/EN 61000-4-5                                 | 1.2/50(8/20) Tr/Th us                                                                                                                                   | L-N                       | B                 |
|                                                               | 1.2/50(8/20) Tr/Th us                                                                                                                                   | L-PE<br>N-PE              | B                 |
| 5 Injected Current<br>IEC/EN IEC 61000-4-6                    | 0.15 MHz to 80 MHz,<br>1000Hz 80%,<br>AM Modulated<br>150 $\Omega$ source impedance                                                                     | CTL/Signal Port           | A                 |
|                                                               | 0.15 MHz to 80 MHz,<br>1000Hz 80%,<br>AM Modulated<br>150 $\Omega$ source impedance                                                                     | AC Power Port             | A                 |
|                                                               | 0.15 MHz to 80 MHz,<br>1000Hz 80%,<br>AM Modulated<br>150 $\Omega$ source impedance                                                                     | DC Power Port             | A                 |
| 6. Power Frequency Magnetic Field<br>IEC/EN 61000-4-8         | 50 Hz,                                                                                                                                                  | Enclosure                 | A                 |
| 7. Volt. Interruptions<br>Volt. Dips<br>IEC/EN IEC 61000-4-11 | Voltage dip 100%<br>Voltage dip 30%<br>Interruption 100%                                                                                                | AC Power Port             | B<br>C<br>C       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## 4.2 GENERAL PERFORMANCE CRITERIA

According to **EN 55035** standard, the general performance criteria as following:

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Criterion A</b> | <p>The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p> |
| <b>Criterion B</b> | <p>During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.</p> <p>After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.</p>                                                                                      |
| <b>Criterion C</b> | <p>Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.</p> <p>Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>                                                                                                                                                                                                                                                                                            |

#### 4.3 GENERAL PERFORMANCE CRITERIA TEST SETUP

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.




**TABLE-TOP EQUIPMENT**

The configuration consisted of a wooden table 0.8 meters high standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A Horizontal Coupling Plane (1.6m x 0.8m) was placed on the table and attached to the GRP by means of a cable with 940k total impedance. The equipment under test, was installed in a representative system as described in section 7 of IEC /EN 61000-4-2, and its cables were placed on the HCP and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

**FLOOR-STANDING EQUIPMENT**

The equipment under test was installed in a representative system as described in section 7 of IEC/EN 61000-4-2, and its cables were isolated from the Ground Reference Plane by an insulating support of 0.1-meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25mm thick, and 2.5meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.

**4.4.3 TEST SETUP**



**HUAK TESTING**  
HUAK TESTING

#### 4.4.4 TEST RESULTS

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.5 °C             | Relative Humidity : | 51%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              |                     |            |
| Test Power :  | DC 24V From Adapter |                     |            |

| Mode            | Air Discharge |   |    |    |   |   |   |   | Contact Discharge |   |    |    |   |   |   |   | Criterion | Result |
|-----------------|---------------|---|----|----|---|---|---|---|-------------------|---|----|----|---|---|---|---|-----------|--------|
|                 | 4             | 8 | 10 | 15 | 2 | 4 | 6 | 8 | 4                 | 8 | 10 | 15 | 2 | 4 | 6 | 8 |           |        |
| Test level (kV) | +             | - | +  | -  | + | - | + | - | +                 | - | +  | -  | + | - | + | - |           |        |
| Test Location   | +             | - | +  | -  | + | - | + | - | +                 | - | +  | -  | + | - | + | - |           |        |
| HCP             |               |   |    |    |   |   |   |   | A                 | A | A  | A  |   |   |   |   | B         | PASS   |
| VCP             |               |   |    |    |   |   |   |   | A                 | A | A  | A  |   |   |   |   |           | PASS   |
| Metallic parts  |               |   |    |    |   |   |   |   | A                 | A | A  | A  |   |   |   |   |           | PASS   |
| enclosure       | A             | A | A  | A  |   |   |   |   |                   |   |    |    |   |   |   |   |           | PASS   |
| slot            | A             | A | A  | A  |   |   |   |   |                   |   |    |    |   |   |   |   |           | PASS   |

Note:

- 1) +/- denotes the Positive/Negative polarity of the output voltage.
- 2) Test condition:  
Direct / Indirect (HCP/VCP) discharges: Minimum 50 times (Positive/Negative) at each point. Air discharges: Minimum 10 times (Positive/Negative) at each point.
- 3) The Indirect (HCP/VCP) discharges description of test point as following:  
1.left side 2.right side 3.front side 4.rear side
- 4) N/A - denotes test is not applicable in this test report

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China





**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

Note:

#### TABLE-TOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC/EN IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

#### FLOOR-STANDING EQUIPMENT


The EUT installed in a representative system as described in section 7 of IEC/EN IEC 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

### 4.5.3 TEST SETUP





## HUAK TESTING

#### 4.5.4 TEST RESULTS

|               |                     |                     |                     |
|---------------|---------------------|---------------------|---------------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000          |
| Temperature : | 23.5 °C             | Relative Humidity : | 51%                 |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18          |
| Test Mode :   | Mode 1              | Test Power :        | DC 24V From Adapter |
| Test Power :  | DC 24V From Adapter | Test Date :         | 2025-12-18          |

| Frequency Range (MHz)                                                                               | RF Field Position | R.F. Field Strength                        | Azimuth                        | Perform. Criteria | Results | Judgment |
|-----------------------------------------------------------------------------------------------------|-------------------|--------------------------------------------|--------------------------------|-------------------|---------|----------|
| 80-1000,<br>1800 ( $\pm 1\%$ ),<br>2600 ( $\pm 1\%$ ),<br>3500 ( $\pm 1\%$ ),<br>5000 ( $\pm 1\%$ ) | H / V             | 3 V/m (rms)<br>AM Modulated<br>1000Hz, 80% | Front<br>Rear<br>Left<br>Right | A                 | A       | PASS     |

### Note:

- 1) N/A - denotes test is not applicable in this test report.
- 2) Criteria A: There was no change operated with initial operating during the test.
- 3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 4) Criteria C: The system shut down during the test.



## 4.6 EFT/BURST TESTING

#### 4.6.1 TEST SPECIFICATION

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Basic Standard:      | IEC/EN 61000-4-4                                  |
| Required Performance | B                                                 |
| Test Voltage:        | Power Line : 1 kV<br>Signal/Control Line : 0.5 KV |
| Polarity:            | Positive & Negative                               |
| Impulse Frequency:   | 5 kHz                                             |
| Impulse Wave shape : | 5/50 ns                                           |
| Burst Duration:      | 15 ms                                             |
| Burst Period:        | 300 ms                                            |
| Test Duration:       | Not less than 1 min.                              |

#### 4.6.2 TEST PROCEDURE

The EUT and support equipment, are placed on a table that is 0.8 meter above a metal ground plane measured 1m\*1m min. and 0.25mm aluminum thickness.



The other condition as following manner:

HUAK TESTING

- a. The length of power cord between the coupling device and the EUT should not exceed 1 meter.
- b. Both positive and negative polarity discharges were applied.
- c. The duration time of each test sequential was 1 minute



### 4.6.3 TEST SETUP



#### Note:

#### TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table (0.8m high) standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system. A minimum distance of 0.5m was provided between the EUT and the walls of the laboratory or any other metallic structure.

#### FLOOR-STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC/EN 61000-4-4 and its cables, were isolated from the Ground Reference Plane by an insulating support that is 0.1-meter thick. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system.



**HUAK TESTING**  
HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

#### 4.6.4 TEST RESULTS

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.7 °C             | Relative Humidity : | 52%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              |                     |            |
| Test Power :  | DC 24V From Adapter |                     |            |

| Coupling Line |        | Test level (kV) |   |   |   |   |   |   |   | Criterion | Result |  |  |
|---------------|--------|-----------------|---|---|---|---|---|---|---|-----------|--------|--|--|
|               |        | 0.5             |   | 1 |   | 2 |   | 4 |   |           |        |  |  |
|               |        | +               | - | + | - | + | - | + | - |           |        |  |  |
| AC line       | L      | A               | A | A | A |   |   |   |   | B         | PASS   |  |  |
|               | N      | A               | A | A | A |   |   |   |   |           | PASS   |  |  |
|               | PE     | A               | A | A | A |   |   |   |   |           | PASS   |  |  |
|               | L+N    | A               | A | A | A |   |   |   |   |           | PASS   |  |  |
|               | L+PE   | A               | A | A | A |   |   |   |   |           | PASS   |  |  |
|               | N+PE   | A               | A | A | A |   |   |   |   |           | PASS   |  |  |
|               | L+N+PE | A               | A | A | A |   |   |   |   |           | PASS   |  |  |
| DC Line       |        |                 |   |   |   |   |   |   |   |           |        |  |  |
| Signal Line   |        | A               | A |   |   |   |   |   |   |           | PASS   |  |  |

Note:

- 1) +/- denotes the Positive/Negative polarity of the output voltage.
- 2) N/A - denotes test is not applicable in this test report
- 3) Criteria A: There was no change operated with initial operating during the test.
- 4) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 5) Criteria C: The system shut down during the test.

**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TEST

HUAK TESTING

## 4.7 SURGE TESTING

### 4.7.1 TEST SPECIFICATION

|                        |                                              |
|------------------------|----------------------------------------------|
| Basic Standard:        | IEC/EN 61000-4-5                             |
| Required Performance   | B                                            |
| Wave-Shape:            | Combination Wave                             |
|                        | 1.2/50 us Open Circuit Voltage               |
|                        | 8 /20 us Short Circuit Current               |
| Test Voltage:          | Power Line : 0.5 kV, 1 kV, 2 kV              |
| Surge Input/Output:    | AC Line                                      |
| Generator Source:      | 2 ohm between networks                       |
| Impedance:             | 12 ohm between network and ground            |
| Polarity:              | Positive/Negative                            |
| Phase Angle:           | 0/90/180/270°                                |
| Pulse Repetition Rate: | 1 time / min. (maximum)                      |
| Number of Tests:       | 5 positive and 5 negative at selected points |

### 4.7.2 TEST PROCEDURE

#### a. For EUT power supply:

The surge is to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks shall not exceed 2m in length.

#### b. For test applied to unshielded unsymmetrical operated interconnection lines of EUT:

The surge is applied to the lines via the capacitive coupling. The coupling /decoupling networks shall not influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks shall not exceed 2m in length.

#### c. For test applied to unshielded symmetrical operated interconnection /telecommunication lines of EUT:

The surge is applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor cannot be specified. The interconnection line between the EUT and the coupling/decoupling networks shall not exceed 2m in length.



**HUAK TESTING**

HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING




HUAK TESTING



HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

#### 4.7.3 TEST SETUP



**HUAK TESTING**

HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 4.7.4 TEST RESULTS

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000 |
| Temperature : | 23.7 °C             | Relative Humidity : | 52%        |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18 |
| Test Mode :   | Mode 1              |                     |            |
| Test Power :  | DC 24V From Adapter |                     |            |

| Coupling Line |      |      | Test level |   |      |   |      |   |      |   | Criterion | Result |  |  |
|---------------|------|------|------------|---|------|---|------|---|------|---|-----------|--------|--|--|
|               |      |      | 0.5 kV     |   | 1 kV |   | 2 kV |   | 4 kV |   |           |        |  |  |
|               |      |      | +          | - | +    | - | +    | - | +    | - |           |        |  |  |
| AC line       | L-N  | 0°   |            |   |      |   |      |   |      |   | B         | PASS   |  |  |
|               |      | 90°  | A          |   | A    |   |      |   |      |   |           |        |  |  |
|               |      | 180° |            |   |      |   |      |   |      |   |           |        |  |  |
|               |      | 270° |            | A |      | A |      |   |      |   |           |        |  |  |
|               | L-PE | 0°   |            |   |      |   |      |   |      |   |           | PASS   |  |  |
|               |      | 90°  | A          |   | A    |   | A    |   |      |   |           |        |  |  |
|               |      | 180° |            |   |      |   |      |   |      |   |           |        |  |  |
|               |      | 270° |            | A |      | A |      | A |      |   |           |        |  |  |
|               | N-PE | 0°   |            |   |      |   |      |   |      |   | B         | PASS   |  |  |
|               |      | 90°  |            | A |      | A |      |   | A    |   |           |        |  |  |
|               |      | 180° |            |   |      |   |      |   |      |   |           |        |  |  |
|               |      | 270° | A          |   | A    |   |      | A |      |   |           |        |  |  |
| DC Line       |      |      |            |   |      |   |      |   |      |   |           |        |  |  |
| Signal Line   |      |      | A          | A |      |   |      |   |      |   |           | PASS   |  |  |


Note:

- 1) Polarity and Numbers of Impulses : 5 Pst / Ngt at each tested mode
- 2) N/A - denotes test is not applicable in this Test Report
- 3) Criteria A: There was no change operated with initial operating during the test.
- 4) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 5) Criteria C: The system shut down during the test.





### 4.8.3 TEST SETUP



#### NOTE:

#### FLOOR-STANDING EQUIPMENT

The equipment to be tested is placed on an insulating support of 0.1 meters height above a ground reference plane. All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.



## HUAK TESTING

#### 4.8.4 TEST RESULTS

|               |                     |                     |                     |
|---------------|---------------------|---------------------|---------------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000          |
| Temperature : | 23.7 °C             | Relative Humidity : | 52%                 |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18          |
| Test Mode :   | Mode 1              | Test Power :        | DC 24V From Adapter |
| Test Power :  | DC 24V From Adapter | Test Date :         | 2025-12-18          |

| Test Ports<br>(Mode)               | Freq. Range<br>MHz) | Field Strength                               | Perform.<br>Criteria | Results           | Judgment |
|------------------------------------|---------------------|----------------------------------------------|----------------------|-------------------|----------|
| Input/ Output<br>AC. Power<br>Port | 0.15 ---10          | 3V(rms) AM Modulated<br>1000Hz, 80%          | A<br>HUAK TESTING    | A                 | PASS     |
|                                    | 10 --- 30           | 3V to 1V(rms) AM<br>Modulated 1000Hz,<br>80% | A                    | A                 | PASS     |
|                                    | 30 --- 80           | 1V(rms) AM Modulated<br>1000Hz, 80%          | A<br>HUAK TESTING    | A<br>HUAK TESTING | PASS     |
| Input/ Output<br>DC. Power<br>Port | 0.15 ---10          | 3V(rms) AM Modulated<br>1000Hz, 80%          | A                    | N/A               | N/A      |
|                                    | 10 --- 30           | 3V to 1V(rms) AM<br>Modulated 1000Hz,<br>80% | A<br>HUAK TESTING    | N/A               | N/A      |
|                                    | 30 --- 80           | 1V(rms) AM Modulated<br>1000Hz, 80%          | A                    | N/A               | N/A      |
| Signal Line                        | 0.15 ---10          | 3V(rms) AM Modulated<br>1000Hz, 80%          | A<br>TESTING         | A<br>HUAK TESTING | PASS     |
|                                    | 10 --- 30           | 3V to 1V(rms) AM<br>Modulated 1000Hz,<br>80% | A<br>HUAK TESTING    | A<br>HUAK TESTING | PASS     |
|                                    | 30 --- 80           | 1V(rms) AM Modulated<br>1000Hz, 80%          | A<br>HUAK TESTING    | A<br>HUAK TESTING | PASS     |

Note:

- 1) N/A - denotes test is not applicable in this Test Report.
- 2) Criteria A: There was no change operated with initial operating during the test.
- 3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 4) Criteria C: The system shut down during the test.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

## 4.9 POWER FREQUENCY MAGNETIC FIELD TESTING

#### 4.9.1 TEST SPECIFICATION

|                      |                         |
|----------------------|-------------------------|
| Basic Standard:      | IEC/EN 61000-4-8        |
| Required Performance | A                       |
| Frequency Range:     | 50Hz                    |
| Field Strength:      | 1 A/m                   |
| Observation Time:    | 1 minute                |
| Inductance Coil:     | Rectangular type, 1mx1m |

#### 4.9.2 TEST PROCEDURE

The EUT and support equipment, are placed on a table that is 0.8 meter above a metal ground plane measured 1m\*1m min. and 0.25mm aluminum thickness.

The other condition as following manner:

- a. The equipment cabinets shall be connected to the safety earth directly on the GRP via the earth terminal of the EUT.
- b. The cables supplied or recommended by the equipment manufacturer shall be used 1 meter of all cables used shall be exposed to the magnetic field.





**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

#### 4.9.4 TEST RESULTS

|               |               |                     |            |
|---------------|---------------|---------------------|------------|
| EUT :         | CM5 AI CAMERA | Model Name :        | ED-AIC3000 |
| Temperature : | N/A           | Relative Humidity : | N/A        |
| Pressure :    | N/A           | Test Date :         | N/A        |
| Test Mode :   | N/A           |                     |            |
| Test Power :  | N/A           |                     |            |

Note: EUT is not belong containing devices intrinsically susceptible equipment, so this test report is not applicable.



HUAK TESTING



HUAK TESTING

HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING



HUAK TESTING




HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING





## HUAK TESTING

#### 4.10.4 TEST RESULTS

|               |                     |                     |                     |
|---------------|---------------------|---------------------|---------------------|
| EUT :         | CM5 AI CAMERA       | Model Name :        | ED-AIC3000          |
| Temperature : | 23.7 °C             | Relative Humidity : | 52%                 |
| Pressure :    | 1010 hPa            | Test Date :         | 2025-12-18          |
| Test Mode :   | Mode 1              | Test Power :        | DC 24V From Adapter |
| Test Power :  | DC 24V From Adapter | Test Date :         | 2025-12-18          |

| Interruption & Dips | Duration (T) | Perform Criteria                                                                           | Results                                                                                    | Judgment                                                                                        |
|---------------------|--------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| Voltage dip 100%    | 0.5          | <b>B</b>                                                                                   |  <b>A</b> |  <b>PASS</b> |
| Voltage dip 30%     | 25           |  <b>C</b> |  <b>A</b> |  <b>PASS</b> |
| Voltage dip 100%    | 250          |  <b>C</b> |  <b>C</b> |  <b>PASS</b> |

Note:

1). N/A - denotes test is not applicable in this test report.

2) Criteria A: There was no change operated with initial operating during the test.

3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.

4) Criteria C: The system shut down during the test.





**HUAK TESTING**



HUAK TESTING



HUAK TESTING



HUAK TESTING





**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

### Electrostatic Discharge



### EFT & Surge & Voltage Dips



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

### Injected Current



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



**HUAK TESTING**

HUAK TESTING



HUAK TESTING



HUAK TESTING

HUAK TESTING



HUAK TESTING

## ATTACHMENT PHOTOGRAPHS OF EUT

Photo 1



Photo 2



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

HUAK TE

HUAK TESTING

HUAK

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Photo 3



Photo 4





HUAK TESTING




Photo 5



Photo 6



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




**HUAK TESTING**

HUAK TESTING

Photo 7



Photo 8



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

Photo 9





Photo 10



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Photo 11





Photo 12





HUAK TESTING

HUAK TESTING



HUAK TESTING




HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING




HUAK TESTING

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Photo 13



Photo 14





HUAK TESTING

HUAK TESTING



HUAK TESTING



HUAK TESTING

HUAK TESTING

Photo 15





Photo 16



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Photo 17





Photo 18



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd., Tel : +86-0755-2302 9901 E-mail: info@huak.com Web : www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhibao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Add.: 1-ZH1, Building B2, Juhuasheng Zhongcheng Innovation Park, Tieping, Futian Street, Bao'an District, Shenzhen, Guangdong, China





HUAK TESTING

NO

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Photo 21





Photo 22





**HUAK TESTING**

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

Photo 23



-----End of report-----

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

**Shenzhen HUAK Testing Technology Co., Ltd.** Tel.: +86-0755-2302 9901 E-mail: [info@huak.com](mailto:info@huak.com) Web.: [www.huak.com](http://www.huak.com)

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China